



*Weight, Size, and Axle configuration adapted to Queensland, Australia road regulations

Mast: MS-WO-TS/79-100/XXX/001

- Mast Clear Height: 79ft/24.1m
- Maximum Static Hook Load: 200,000 lbs/645 kn (6 lines strung)
- Drill Line: 1 1/25.4 mm
- Travelling block: 100 ton Mckissick
- Power Swivel: Venturetech XK90
- Winches: -TH3 (7,250lb) Qty: 2x
-PL1 (1,100lb) Qty: 1x
- Roughneck: Rangeland Automated Powertong PH-15
- Drill Floor: Collapsible, Height adjustable (8'-20')
- Accessories: -Swingout Mast Boom
-Lube Tube Stored in Mast
-Stowable Drillers Console in C-Frame

Substructure: SB-WO-TR/20-100/XXX/002

- Trailer: Split-Quad w/ Tandem Jeep & Booster
- Drawworks: Sparta Fast540db
- Engine: 550 HP Detroit Diesel Series 60
- Levelling: -Front and Rear Levelling Jacks capable of levelling slopes from 2.38° downwards to 3.82° upwards.
-Rear Telescoping Stabilizer Jacks

TRS104 CENTERPIECE



*Designed & Manufactured to API 4F.